

173 Moo9 Malaiman Road, Tumbon Tapluang, Amphur Muang Nakornphathom 73000 Thailand TEL.: +6697449 4626 E-mail:salesco@thaiformosa.com Tax ID.: 010 553 105 73 41

## PRODUCT SPECIFICATION

Black PP geotextile: PP geotextile acts as a barrier between different soil layers, preventing them from mixing and compromising the stability of the structure. This is useful in roads, pavements, and foundations to prevent coarse and fine-grained soils from intermixing.



Tape Yarn	Denier (g/9,000 m)		Width (mm)	
Main Body	Target	Tolerance	Target	Tolerance
Warp	3400	± 2%	6.0	5.7 - 6.3 mm
Weft (multifilament)	2400	± 2%	1.0	0.9 - 1.1 mm
Construction	Target		Tolerance	
Construction (Tape/inch)	16x17		16x17 ± 1 tape	
Mass ( Main Body)	440 g/m²		400 - 450 g/m²	
		- 1.		

**Fabric edges**Tuck in selvedge

Properties	Standard	Specification
Tensile Strength		
<ul> <li>Warp</li> </ul>	AS 2001.2.3	≥ 398.00 kgf
• Weft	AS 2001.2.3	≥ 398.00 kgf
Elongation		
<ul> <li>Warp</li> </ul>	AS 2001.2.3	≥ 30.00 %
• Weft	AS 2001.2.3	≥ 30.00 %
Weathering Test	ASTM G-154	≥ 5 Years







